

W5500XH 0.88mm ultra-thin bezel seamless video wall

1920x1080 full HD, LED backlight



Features:

- 55" industrial grade A plus TFT LCD display, LED backlight
- 0.88 mm screen to screen gap in total
- 1920x1080 full HD resolution (16:9),
- 1200:1 High contrast ratio,
- 700 cd/m² high brightness ,
- Over MTBF 60,000 hours above lifespan, 7x24 hours working,
- Multi-windows, PIP & POP, one image across multiple screens

Technical Parameters:

Model	W5500XH
Panel size	55" TFT-LCD,LED backlight
Bezel width	Right, bottom: 0.44mm
	Left, top:0.44mm
	Bezel width in total: 0.88mm
Colors	16.7M
Resolution	1920x1080 (16:9),
Pixel Pitch	0.63×0.63mm
Brightness	700cd/m ²
Contrast Ratio	1200:1
View angle	178°/178°
Response time	8ms
Material of housing	Metal
Color of housing	Black
Systems	PAL/NTSC/SECAM
Operation method	Remote controller optional
SATA interface (Control signal)	RS232 (RJ45-8)
SATA loop-out(Control signal)	RS232 (RJ45-8)
OSD languages	Chinese, English, multi-languages optional
HDMI input	1xHDMI
DVI input	1xDVI
VGA input	1xVGA(D--SUB 15PIN)
AV input	1xBNC (CVBS in)
AV output	1xBNC (CVBS out)
Frequency	50Hz, 60Hz ,70Hz
Power supply	AC100~240V,50/60Hz
Power consumption	≤230W
Standby power consumption	3W
Operation temperature	0°C~50°C
Storage temperature	Minus 20°C~+60°C
Operation & Storage humidity	20%~80%
Installation methods	Embedded, wall-mount,
Dimension of unit screen	1210.5*681.2*114mm (Not including wall-mount brackets)
Net weight of unit screen	28.2kg
Gross weight of unit screen	43.9kg (1 piece packaging)

Fultape Electronics Co., Limited

NO. 2 BLDG., Sanlian Industrial Park, No.2045 Songbai Rd.,

Shiyan Sub-Dist., Bao'an Dist., Shenzhen,China

Email: overseas@fultape.com Tel.: +86-755- 2350 0700 2350 0200 Fax:+86-755-2319 2637 <http://www.fultape.com>